

CU-420FO DATA SHEET



Model: CU-420FO Speaker Catagory: Column Made in: Korea Color: Black Standard: Industrial Standard Protection Rating: IP34

GENERAL INFORMATION:

Ideal for indoor use		
Installation height:	3 to	3.5m
Max. Coverage Distance	e:	20m
Distance from Speaker: 1000m², 6 x Speakers (Noisy 85dB Tap @ 20W)		
Area Coverage per speaker: 170m²		

PURPOSE OF USE:

Public Address, Voice announcement and high quality background music applications.

CU-420FO | 20W Outdoor Column Speaker

The CU-420FO 20W Column Speaker is the latest addition to the Inter-M speaker range. The speaker has 20W power and 100v. The new CU-420FO high-quality Column Loudspeakers featuring rich sound quality, improved frequency response for public address, background music and AV applications. Quality and Durability has been tested by KS (Korean Industrial Standards speaker). Product passing a verity test including a 100 hours full power noise, high temperature, low temperature, humidity are assigned with 'PASS' to provide a stable and equal quality in the market.

PRODUCT FEATURES:

20W 100v line
Proofed drivers/loudspeakers for use in damp environments
Robust construction
Multi-poisition mounting bracket
100v power taps (rated and half power)
Screw terminal connections

SPECIFICATION:

Type:	2 x 4" Full-range Column Speaker		
Input Power:	100V	20/10W	
Impedance:	100V	500/1kΩ	
Frequency Response(-10dB):		150Hz ~ 16.9kHz	
Frequency Range(-20%):		120Hz ~ 20kHz	
Sensitivity (1W/1m, 1kHz):		89dB	
Maximum SPL[Cont]:		102dB	
Nominal Dispersion	1kHz	203° x 99°	
Conical:	4kHz	95° x 25°	
Weight (Net):		3.13kg	
Dimensions (WxHxD, mm) :		156 x 400 x 129	

SUITABLE APPLICATION AREA:

Bus/Railway Stations, Garments and Production Industries, Tunnel / Corridors etc.